

CO₂ MOBILE FIRE EXTINGUISHERS



PRODUCT DESCRIPTION

NAFFCO Mobile CO₂ fire extinguishers are characterized by their high performance and simple method of operation. They are suitable for fires involving flammable liquids, gases and electrical equipment. Effective for Class B, C & E. Suitable for Class B fire risks.

FEATURES

- The Fire Extinguishers are designed to comply with the specifications and requirements of BSEN 1866-1.
- Kitemark approved.
- High-grade brass head valve ensures reliability and Discharge outlet is controlled by High Pressure Ball Valve.
- Cylinder assembly compliance to council directive 2014/68/EU (PED) is certified by BSI(2797).
- Cylinders are compliance to council directive 2010/35/EU (TPED) is certified by TUV
- High gloss polyester powder painted UV stabilized after shot blasting ensures corrosion resistance under extreme conditions.
- Safety valve is fitted in each extinguisher for maximum safety.
- Discharge nozzle designed to produce a jet of extinguishing gas.



SPECIFICATION

Model Number	NTC 10X	NTC 30X
Extinguisher Capacity	10 kg	30 kg
Fire Rating	70B	113B
Working Pressure	55 - 60 bar @ 25°C	55 - 60 bar @ 25°C
Maximum Operating Pressure	174 bar @ 60°C	174 bar @ 60°C
Test Pressure	250 bar	250 bar
Total Height & Width	1,435 x 440 mm	1,095 x 675 mm
Total Weight	52 kg	125 kg
Range of Discharge	6-8 m	6-8 m
Duration of Discharge	19 - 21 sec.	42 - 45 sec.
Operating Temperature	-20°C to +60°C	-20°C to +60°C
Propellant	Self Propellant	Self Propellant
Hose Size & Length	Bore 3/8" x 5 m	Bore 3/8" x 5 m
Cylinder Material	Carbon Steel	Carbon Manganese Steel