#### **INTERFACE PLUS**

#### 81028-M00-GA330

Description: Unlined nitrile gloves, 11mil

Features &

\* Anti-slip pattern for good grip in wet and dry conditions

Benefits:

\* Chlorine washed\* Compliant with (EC) No.1935/2004,EU 10/2011 & BFR XXI

(Blue, Green, White, Yellow)

\* Ingredients comply with FDA regulations for food contact (Blue, Green only

)

\* Manufactured under a stringent quality management system

\* Nitrile rubber for better chemical resistance

\* Improved abrasion resistance

\* Straight cuff

Applications: Food Industry, Laboratories, Printing Industry, Facility maintenance

Elastomer: Nitrile rubber
Thickness: 0.28 +/- 0.05 mm
Lining: Unlined chlorinated
Former: Reverse Lozenge, CVIL

Exterior: Chlorinated Cuff Types: Straight

Treatments:

Colours: Blue B14, Green G34, Green G8, Yellow Y2, Orange O20, Green G39

AQL - Critical: 1.5 Major: 4.0

CE Certification: Conforms to requirements of the PPE Regulation (2016/425) as brought into UK Law and amended as a Category

III product, Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN ISO

21420:2020

Conforms to: ASTM D4679 of 2021

Physical	Size	Palm	Wrist	Cuff	Length
Dimensions:	6	195	185	284	330
	7	214	206	296	330
	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330

Circumference in mm, +/- 10 mm Tol. +/- 10 mm

Shelf Life 5 Years

EN 374-4

Protection against Chemical h	Performance	Degradation %	
EN ISO 374-1/TYPE A			
	* Methanol (A)	Level 1	81.7
( ),	* n-Heptane (J)	Level 6	30.4
	* Sodium hydroxide 40% (K)	Level 6	-9.6
(I)	* Sulphuric acid 96% (L)	Level 2	88.1
JKLMNOPST	* Nitric acid 65% (M)	Level 2	98.7
	* Ammonium hydroxide 25% (O)	Level 4	46.7
Note: Printed copies are valid only	on the date printed		Revision:15
nted Date: 29-Nov-2023		Published	Date: 28-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964 Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

## **INTERFACE PLUS**

# 81028-M00-GA330

* Hydrogen peroxide 30% (P)	Level 6	22.2
* Formaldehyde 37% (T)	Level 6	12
* Hydrofluoric acid 40% (S)	Level 3	X
* Acetic acid 99% (N)	Level 2	95.1

## Protection against Mechanical hazards

EN 388



* Abrasion resistance	Level 3
* Blade cut resistance	Level 0
* Tear resistance	Level 0
* Puncture resistance	Level 1
* TDM cut resistance	X

# Protection against Micro-organisms risk



\* Protection against bacteria and fungi

\* Protection against viruses

Pass

Performance

Performance

n/a

Note: Printed copies are valid only on the date printed

Revision:15 Printed Date: 29-Nov-2023 Published Date: 28-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka Phone: +94-0122-683-964 Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com