NOVA 35 X

62035-M00-AA290B

Description: Ultra light weight bead rolled flock lined natural rubber gloves

Features & Benefits:

* Anatomically shaped for comfort

* Anti-slip pattern for good grip in wet and dry conditions

* Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length

* Compliant with (EC) No.1935/2004, EU 10/2011 & BFR XXI

(Red, Yellow)

* Improved sensitivity and dexterity

* Natural rubber

* Pure cotton lining to absorb perspiration

Applications: Agriculture, Food Industry, Household Purposes, Pharmaceutical, Facility maintenance

Elastomer: Natural rubber
Thickness: 0.35 +/- 0.05 mm
Lining: Flocklined

Former: Honeycomb CIH
Exterior: Finished smooth
Cuff Types: Bead rolled
Treatments: Un-chlorinated

Colours: Blue B1, Pink P2, Red R1, Red R5, Yellow Y1

AQL - Critical: 1.5 Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment

against standards EN ISO 21420:2020, EN 388:2016 + A1:2018, EN 421:2010(excluding clause 4.3)

Conforms to: ASTM D4679 of 2021

Physical Size Palm Wrist Cuff Length Dimensions: 194 180 244 290 6-6.5 7-7.5 204 183 245 290 290 8-8.5 212 196 260 9-9.5 230 221 279 290 XL245 230 290 300

Circumference in mm, +/- 5 mm

Shelf Life 3 Years

EN 374-4

Protection against Chemical hazards		Performance	Degradation %
EN ISO 374-1/TYPE B			
	* Sodium hydroxide 40% (K)	Level 6	0.7
	* Nitric acid 65% (M)	Level 4	15.2
	* Hydrogen peroxide 30% (P)	Level 1	1.7
KMT	* Formaldehyde 37% (T)	Level 6	2.7

Tol. +/- 10 mm

Note: Printed copies are valid only on the date printed

Printed Date: 04-Jul-2024

Published Date: 31-Jan-2024

No: 400, Deans Road, Colombo 10, Sri Lanka Phone: +94-0122-683-964 Fax: +94-0122-699-018

Fax: +94-0122-699-018 E-Mail: postmast@dplgroup.com



Revision:11

NOVA 35 X

62035-M00-AA290B

Protection against Mechanical hazards

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 1

Performance

Level 0

Level 0

Level 0 X

Performance

Protection against Micro-organisms risk

EN ISO 374-5



* Protection against bacteria and fungi

* Protection against viruses

Pass

n/a

Note: Printed copies are valid only on the date printed

Printed Date: 04-Jul-2024



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964 Fax: +94-0122-699-018

Published Date: 31-Jan-2024

E-Mail: postmast@dplgroup.com

Revision:11