

CODE: MBK14-250PA-WLD

ERP: 0135339

Trolley Fire Extinguisher 25Kg Dry Powder Welded Trolley

25Kg Dry Powder Welded Trolley Fire Extinguisher with 5m Discharge Hose and High Strength Wheels.
Pressure Gauge Safety Release Valve.

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	CNBOP, GTC, IGSU, ITALY, MIRTEC
Extinguisher Type	Trolley
Pressure Type	Stored Pressure
Suppression Agent Type	Powder
Capacity	25 Kg
Extinguishing Agent	ABC40%
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	28 bar
Volume of Equipment	31 L
Cylinder Height	520±5 mm
Cylinder Diameter	305±3 mm
Cylinder Neck Thread	G2
Valve Material	HPb59-1 (Nickel Plated)
Cylinder Material	HP295
Safety Valve	22-28 bar
Approx. gross Weight	60 kg
Approx. Dimensions	950x550 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



Issue Date: 21/11/2024

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com