SAFETY JOGGER
INDUSTRIAL

Medium

CERES S3

Women's Leather Safety Shoes

CERES nubuck safety shoes for women with slipresistant outsole, composite toe and SJ Flex puncture resistance deliver lightweight comfort and protection.

Upper	Nubuck Action Leather
Lining	3D-Mesh
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Anti-Puncture Textile
Outsole	Rubber (NBR)
Toecap	Composite
Category	S3 / SRC, HRO
Size range	EU 36-42 / UK 3.5-8.0 / US 6.0-10.5 JPN 22.5-26.5 / KOR 235-270
Sample weight	0.470 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011

210

S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

Composite toecap
Metalfree and lightweight, no thermal or electrical conductivity

SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.

Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.

SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:
Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Mining, Logistics, Oil & Gas, Industry

Environments:
Dry environment, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	**Nubuck Action Leather**			
	Upper: permeability to water vapor	mg/cm^2/h	3.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm^2	27.3	≥ 15
Lining	**3D-Mesh**			
	Lining: permeability to water vapor	mg/cm^2/h	86.9	≥ 2
	Lining: water vapor coefficient	mg/cm^2	695.4	≥ 20
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	**Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	mm^3	82.6	≤ 150
	Outsole slip resistance SRA: heel	friction	0.34	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.36	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.22	≥ 0.18
	Antistatic value	MegaOhm	24.5	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	24	≥ 20
Toecap	**Composite**			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	18.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.